

Custom designed Soldering Tips can be made on special request with MOQ.



Model DSS25A (Analog)



Model DSS25D (Digital)

Specifications

Parameters	DSS25D	DSS25A
Display	Digital	Analog
Power	80 Watt	
Input Supply	230VAC, 50Hz	
Temperature Range	200°C ~ 450°C	
Tip to Gnd Potential	<2mV	
Tip to Gnd Resistance	<2Ω	
Dimensions (approx.)	83x140x125mm	

Scope of Supply

- Power & Control Unit
- Soldering Pencil fitted with Soldering Tip
- Soldering Pencil Holder & Cleaning Sponge

Features

- High Quality Ceramic Heating Element
- Lightweight handle for long duration use
- Digital display for Digital Stations

Variety of Soldering Tips for various soldering applications (Common for all above Models)

Description	Diagram	Width A (mm)	Thickness B (mm)	Model
Chisel Tip		0.8	0.5	T-0.8D
		1.6	0.5	T-1.6D
		2.4	0.5	T-2.4D
		3.2	0.5	T-3.2D
		4.8	0.5	T-4.8D
Pointed Tip		R0.5	-	T-B
Sloped Tip		Ø3	-	T-3C
		Ø4	-	T-4C
SMD Tip		5	2	T-K

shown trademarks are property of their respective owners.

While the information contained herein in, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.