

for heat shrinking, drying and reworking of SMD components on PCBs



Features

- Controlled gentle hot airflow makes it ideal for rework of miniature SMD chips, SOTs, SOICs.
- Different Hot Air Nozzles available for reworking of different types SMD components
- Push Buttons for precise temperature control
- Suitable for reworking of Leadfree components
- Induction Switch in Handle ensures automatic starting when in use. This feature saves electrical energy and prolongs the life of heating element.
- Compact and durable, takes up little space.
- Reliable Brushless Fan with very low noise


Specifications

- Power : 700 Watt
- Input Supply : 230 VAC, 50 Hz
- Temperature Range : 100°C ~ 450°C
- Airflow type : Brushless fan
- Air Volume : 120 litre/minute (Max.)
- Display type : Digital, LED
- Dimensions (approx.) : 138 x 100 x150 (mm)
- Weight (approx.) : 1.7 Kg

Scope of Supply

- HAS58D Main Control Unit
- Hot Air Pencil with Round Nozzle

Various Hot Air Nozzles available for Model HAS58D Hot Air Rework Station



shown trademarks are property of their respective owners.

While the information contained herein in, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.