

Ready-to-use Hi-Quality ESD Safe Table Mats as per your size



: 4 ~ 6Mpa

: 250%

: 120°C

Creates ESD Safe environment against damaging static charges

2-Layer ESD Rubber Mats have a top layer of static dissipative rubber layer laminated to a black conductive rubber bottom layer. Surface resistivity of the top layer is $10^6 \sim 10^9$ ohm and the bottom layer is 10³~10⁵ ohm. Our 2-Layer ESD Rubber Mats are resistant to commonly used solvents in electronics assembly/repair work.

These Table Mats are strongly recommended as first basic requirement when setting-up ESD Safe Workstation for electronic assembly/repair/field servicing. ESD Safe working environment is neccessary to protect expensive micro-electronic devices.

Specifications:

- Resistivity of surface layer
- Resistivity of bottom layer
- Wear rate
- Electrostatic dissipation time
- Impact Brittleness Temperature (no incision)
- :<0.1s : -250°C without

: 0.02g/cm²

destruction

 $: 10^{6}\Omega \sim 10^{9}\Omega$

: 10³Ω ~ 10⁵Ω



Hi-end Top most quality type long lasting ESD Safe Rubber Mats



Thickness

- Tensile strength
- Elongation at break
- Tear Strength (Right Angle Type) : 20.6KN/m
- Temperature resistance



Cheap and Low quality type ESD Safe Rubber Mats

We specialize in supplying ready-to-use ESD Safe Table Mats as per sizes of customers Following sizes are what we are supplying commonly to many customers at present We also supply Full Rolls of these ESD Safe Table Mats in 0.9x10 & 1.2x10 meter sizes

		Part Number	Size (Feet)	Part Number	Size (Feet)
		ESDTM-0203	2 x 3	ESDTM-0304	3 x 4
		ESDTM-0204	2 x 4	ESDTM-0305	3 x 5
	10mm Snap Button to connect Wrist Strap	ESDTM-0205	2 x 5	ESDTM-0306	3 x 6
600	and Grounding Cord	ESDTM-0206	2 x 6	ESDTM-0307	3 x 7
	JUNNY	ESDTM-0207	2 x 7	ESDTM-0308	3 x 8
	Top Most Quality	ESDTM-0210	2 x 10	ESDTM-0312	3 x 12
		ESDTM-0215	2 x 15	ESDTM-0315	3 x 15

We also stock for immediate delivery following accessories for our ESD Safe Table Mats

Grounding Cord

- Designed to ground ESD Table Mats Provides two grounding points, one for Wrist Strap & other for
- connection to ground One end has Snap Button & 2 Banana Jacks; other
- end has Grounding Thimble
- Length: 2 meters (approx.)

shown trademarks are property of their respective owners.

P/N: IGC-1601



ESD Safe Wrist Strap

P/N: IWSESD-1602

- Elastic Polyester Fabric with conductive plated threads
- In-built 1 MOhm resistor
- · Length of Cord: 6 feet
- Snap Button at one end & Banana Plug with Alligator Clip at other end



Warranty is 12 months from the date of invoice. It excludes any mechanically damaged part.

While the information contained herein in, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existin patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvement

1