

Super Fine Mesh 2 mm width Desoldering Wick

P/N: ZD-180

- High quality Desoldering Wick with no clean flux
- Pure oxygen-free copper wire
- Width: 2mm
- Length: 1.5 meter



Super Fine Mesh 0.5 mm width Desoldering Wick

P/N: IDW-0.5

- High quality Desoldering Wick with no clean flux
- Pure oxygen-free copper wire
- Width: 0.5mm
- Length: 1.5 meter



Flux Application Bottle with Soft Brush

P/N: IFABB-60

- Dispenses flux smoothly
- Integrated soft dispensing brush for smooth application of flux.
- Cap to cover the brush (when not in use) to avoid evaporation of flux.
- Capacity: 60 ml



Weller Tip Activator

for prolonging the life of Soldering Tips

- Regular use will prolong the life of Soldering Tips.
- It is compatible with leadfree and non-leadfree solders
- Rotate the hot soldering tip on solid paste surface for regeneration.



Note: There is no shelf life for this

Pre-Cut Cleaning Sponges

P/N: ICS-XXXX

- Replacement Sponges for Soldering Stations
- Cleans surface oxidation from Soldering Tips
- Made from natural cellulose
- Does not stick on the Soldering Tips
- High temperature resistant
- Available Sizes:
 - P/N: ICS-5570 (55 x 70 mm)
 - P/N: ICS-3050 (30 x 50 mm)

How to use these Cleaning Sponge:

- Dip the Sponge in water and squeeze it maximum to achieve moist sponge.
- Only moist sponge cleans the soldering tips thoroughly.
- Excess water in the sponge will damage the Soldering Tips



Dry Metal Wool type Tip Cleaner for Soldering Tips

P/N: ISTC-1615

This Solder Tip Cleaner is perfect tool for cleaning the hot Soldering Tips without decreasing the temperature of soldering tip while cleaning, as happens in normally while cleaning with wet sponges

- Made from brass wire and comes with a convenient holder for easy use.
- It features low abrasive brass wire which helps to clean the Soldering Tips thoroughly.



There is no warranty for these consumable items.

While the information contained herein in, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.

shown trademarks are property of their respective owners.