



## **Scope of Supply**

- DDS01 Power & Control Unit
- DDP01 Desoldering Gun
- Desoldering Bit
- Heavy Duty Support Rack
- Cleaning Sponge
- · Operating Manual

## **Specifications**

Input Supply : 230 VAC, 50Hz

Heating Power : 90 Watt

Temperature Range : 200°C ~ 450°C
Vacuum Pressure : 600mm Hg

• Tip to Ground Potential : <2mV

• Tip to Ground Resistance : <2 Ohm

## **Desoldering Nozzles for DDS01 Desoldering Station**





P/N	Ø A mm	ØB mm
A1005	1.0	2.5
A1006	1.3	3.0



## Assured availability, normally ex-stock, of Spare Parts of Desoldering Gun







SN	Description	Remarks
1	Barrel & Nut Assembly	Whenever required
2	Desoldering Nozzle	Replace if worn out
3	Heating Element	Replace when display shows H-E/S-E
4	Spring Filter	Replace if damaged

SN	Description	Remarks
5	Filter Pipe	Replace if damaged
6	Ceramic Paper Filter	Replace look yellow in colour
7	Filter pipe Assembly	Replace if damaged
8	External Filter	Replace if suction is less

Warranty is 12 months from the date of invoice. It excludes all consumable parts as Heating Elements, Temperature Sensors, Soldering/Desoldering/Hot Air Tips, Cleaning Sponges, Cleaning Brass Wool

shown trademarks are property of their respective owners

While the information contained herein in, has been carefully compiled to the best of our knowledge, nothing is intended as representation and warranty on our part; and no statement shall be construed as recommendation to infringe any of existing patents. We accept no liability of whatsoever for any faults and errors in the information contained herein. Contents of this catalogue and specifications of the products, are subject to change without notice due to continuous improvements.